Printing date 08.02.2023 Revision: 08.02.2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MR® 62 Penetrant red

**Aerosol** 

- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Life cycle stages

F Formulation or re-packing

IS Use at industrial Sites

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Product category PC14 Metal surface treatment products
- · Process category

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC13 Treatment of articles by dipping and pouring

· Environmental release category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

- · Article category AC7 Metal articles
- · Application of the substance / the mixture

Testing material for nondestructive surface crack detection

#### · 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

3AK Chemie Pvt. Ltd.

5/B5/1 - TSIIC Automotive Park,

Kallakal, Telangana, INDIA

Dist: Medak Pin: 502336

Email: qc@3akchemie.com

#### · Further information obtainable from:

3AK Chemie Pvt. Ltd. Safety Data Sheet, gc@3akchemie.com

### · 1.4 Emergency telephone number:

24h- Emergency Contact Phone Number

For Chemical Emergency, Spill, Leak, Fire, Exposure or Accident Call Day or Night within USA and Canada: 1 800 424 9300 Outside USA and Canada: 001 703 527 3887

In-Country Emergency Number for:

Germany: 0800-181-7059

 Australia:
 +61 433 289 052
 (English)

 Hong Kong:
 800 968 793
 (Cantonese)

 India:
 000 800 100 7141
 (Hindi)

 South Africa:
 0 800 983 611
 (English)

(WISAG FMO Cargo Service GmbH & CO.KG)

#### **SECTION 2: Hazards identification**

#### · 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

#### · 2.2 Label elements

### · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 08.02.2023 Revision: 08.02.2023

Trade name: MR® 62 Penetrant red

Aerosol

(Contd. of page 1)

#### · Hazard pictograms



### · Signal word Danger

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

**Precautionary statements** 

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### · Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

· **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-47-8 EINECS: 265-149-8 Reg.nr.: 01-2119484819-18-XXXX	Distillates (petroleum), hydrotreated light Asp. Tox. 1, H304	50-70%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-XXXX	propane Flam. Gas 1, H220 Press. Gas C, H280	10-25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119486944-21-XXXX	butane Flam. Gas 1, H220 Press. Gas C, H280	10-25%
CAS: 84961-40-0 EINECS: 284-628-2	Amine, C10-14 verzw. u. lineare Alkyl-Bis(2,4-dihydro-4-((2-hydroxy-5-nitrophenyl)azo)-5-methyl-2-phenyl-3H-pyrazol-3-onato(2-))chromat(1-)(1-) Acute Tox. 4, H302	1-5%

· Propellant: Propane-Butane

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Printing date 08.02.2023 Revision: 08.02.2023

Trade name: MR® 62 Penetrant red

Aerosol

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: Not relevant aerosol can.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Information for doctor:

Grease with skin-cream to restore fat film in order to prevent skin inflammation.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

5.1 Extinguishing media

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

#### **SECTION 6: Accidental release measures**

## · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, e.g. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.

(Contd. on page 4)

Printing date 08.02.2023 Revision: 08.02.2023

Trade name: MR® 62 Penetrant red

**Aerosol** 

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- Respiratory protection:

For good ventilation provide, this can be achieved by local or space exhaust. If the concentration lies over the job limit values, then, a certified respirator suitable for this purpose must be used. Filter AX-P2

#### · Protection of hands:

Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.5 \text{ mm}$ 

### Penetration time of glove material

Value for the permeation: Level  $\leq 4$  Supplier for suitable protection gloves: ASD ArbeitsSicherheit Dortmund

Torstr. 101 - 37355 Niederorschel OT Rüdigershagen

Tel.: 02301 / 919543 - Fax: 02301 / 9453893

E-Mail: m.schnellhardt@t-online.de - http://www.arbeitssicherheitdortmund.de

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye protection: With danger of the eye contact closing eye protector.
- Body protection: Protective work clothing

## **SECTION 9: Physical and chemical properties**

## · 9.1 Information on basic physical and chemical properties

- General Information
- · Appearance:

Form: Aerosol Colour: Red

Odour: CharacteristicOdour threshold: Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

(Contd. on page 5)

Printing date 08.02.2023 Revision: 08.02.2023

Trade name: MR® 62 Penetrant red

Aerosol

	(Contd. of page
Initial boiling point and boiling range	: Not applicable, as aerosol.
Flash point:	-97 °C
·	Basis: propellant
Flammability (solid, gas):	Not applicable.
Ignition temperature:	Not determined - aerosol.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.5 Vol %
Upper:	10.9 Vol %
Vapour pressure at 20 °C:	8300 hPa
	Basis: propellant
Density at 20 °C:	0.98 g/cm <sup>3</sup>
•	Basis: active substance
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Organic solvents:	30.0 %
9.2 Other information	No further relevant information available.

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

Danger of bursting of the aerosol can during overheating

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

### 106-97-8 butane

Inhalative LC50/4 h 658 mg/l (rat)

(Contd. on page 6)

Printing date 08.02.2023 Revision: 08.02.2023

Trade name: MR® 62 Penetrant red

**Aerosol** 

(Contd. of page 5)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Water hazard class 1: weakly water-endangering

- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Eliminate in accordance with local regulations.

· Waste disposal key:

For this product no waste key number can be specified, because only the intended purpose permits an allocation. The waste key number is to be specified in arrangement with the regional waste disposal.

- Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information			
· 14.1 UN-Number			
· ADR, IMDG, IATA	UN1950		
14.2 UN proper shipping name			
ADR	1950 AEROSOLS		
· IMDG	AEROSOLS		
· IATA	AEROSOLS, flammable		

(Contd. on page 7)

Printing date 08.02.2023 Revision: 08.02.2023

Trade name: MR® 62 Penetrant red

Aerosol

(Contd. of page 6) · 14.3 Transport hazard class(es) · ADR 2 5F Gases. · Class · Label 2.1 · IMDG, IATA 2.1 · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: Not applicable. · 14.6 Special precautions for user Warning: Gases. · Danger code (Kemler): · EMS Number: F-D,S-U SW1 Protected from sources of heat. · Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of · Segregation Code 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity · Transport category · Tunnel restriction code D · IMDG · Limited quantities (LQ) 1L · Excepted quantities (EQ) Code: E0 Not permitted as Excepted Quantity

(Contd. on page 8)

Printing date 08.02.2023 Revision: 08.02.2023

Trade name: MR® 62 Penetrant red

Aerosol

(Contd. of page 7)

UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

#### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Waterhazard class:

Water hazard class 1: slightly hazardous for water.(In accordance with classification VwVwS,appendix 4)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

The data in this safety data sheet are based on our knowledge at the time of the revision. The information should give you reference points for a safe handling of the product specified in this safety data sheet. The data are not transferable to other products. If the product specified in this safety data sheet is mixed or processed with other materials, the data cannot be transferred without examination.

#### Relevant phrases

The wording of the listed risk phrases are those of the individual raw materials.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

#### · Recommended restriction of use

Existing national and local laws concerning chemicals are to be considered.

- · Department issuing SDS: 3AK Chemie Pvt. Ltd.
- · Contact: 3AK Chemie Pvt. Ltd., Safety data sheets, Email: qc@3akchemie.com
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Press. Gas C: Gases under pressure – Compressed gas

Acute Tox. 4: Acute toxicity – Category 4
Asp. Tox. 1: Aspiration hazard – Category 1

\* Data compared to the previous version altered.