Version number 1 Printing date 27.05.2024 Revision: 27.05.2024

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: MR® 703 W Developer white
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Life cycle stages

F Formulation or re-packing

IS Use at industrial Sites

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category PC14 Metal surface treatment products

Process category

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC13 Treatment of articles by dipping and pouring

· Environmental release category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

· Article category AC7 Metal articles

· Application of the substance / the mixture

Testing material for nondestructive surface crack detection

# · 1.3 Details of the supplier of the safety data sheet

# Manufacturer/Supplier:

MR Chemie GmbH

Nordstr. 61-63

59427 Unna (Germany)

Tel. +49 (0)2303 95151 0

Fax: +49 (0)2303 95151 10

post@mr-chemie.de

www.mr-chemie.de

## · Further information obtainable from:

MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38, QS@mr-chemie.de

## 1.4 Emergency telephone number:

24h- Emergency Contact Phone Number For Chemical Emergency, Spill, Leak, Fire, Exposure or

Accident (WISAG FMO Cargo Service GmbH & CO.KG)

Call Day or Night within USA and Canada: 1 800 424 9300

Outside USA and Canada: 001 703 527 3887

In-Country Emergency Number for:

0800-181-7059 Germany:

China: (Mandarin) 4001 204937 Hong Kong: 800 968 793 (Cantonese) India: 000 800 100 7141 (Hindi) 0 800 983 611 South Africa: (English)

# **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The mixture is classified according to Regulation (EC) No 1272/2008 according to the most recent

The product is not classified, according to the GB CLP regulation.

#### · 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void

(Contd. on page 2)

Printing date 27.05.2024 Version number 1 Revision: 27.05.2024

Trade name: MR® 703 W Developer white

(Contd. of page 1)

#### · Additional information:

EUH208 Contains 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

EC number: 931-960-7 C10 Alcoholethoxylate

Eye Irrit. 2, H319

1 - 5%

Additional information:

Wording of the listed hazard phrases are indicated in section 16 and relate to individual raw components.

### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:

Grease with skin-cream to restore fat film in order to prevent skin inflammation.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

## · 5.1 Extinguishing media

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

### Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)

Printing date 27.05.2024 Version number 1 Revision: 27.05.2024

Trade name: MR® 703 W Developer white

(Contd. of page 2)

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling Open and handle receptacle with care.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Condition of the tanks and stockrooms is to be co-ordinated with the responsible authorities. Keep receptacles tightly sealed.

- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Protect from heat and direct sunlight.
- · Recommended storage temperature: 5 45°C, 41 113 °F
- 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- · Additional information about design of technical facilities: No further data; see section 7

Additional informat	ion about design of technical facilities: No further data; see section 7.		
· Ingredients with lin	nit values that require monitoring at the workplace:		
102-71-6 2,2',2"-nitr	ilotriethanol		
MAK (Germany)	Long-term value: 5E mg/m³		
141-43-5 2-aminoet	hanol		
IOELV (EU)	Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Skin		
WEL (Great Britain)	Short-term value: 7.6 mg/m³, 3 ppm Long-term value: 2.5 mg/m³, 1 ppm Sk		
AGW (Germany)	Long-term value: 5.1 mg/m³, 2 ppm 2(I);DFG, EU, H, Y, Sh		
2634-33-5 1,2-benzi	sothiazol-3(2H)-one		
MAK (Germany)	vgl.Abschn.IIb		
· DNELs			
102-71-6 2,2',2"-nitr	ilotriethanol		
Dermal Long-term	n - systemic effects, worker 6.3 mg/kg bw/day (worker)		
Inhalative Long-term	n - systemic effects, worker 5 mg/m³ (worker)		
Long-term	n - local effects, worker 5 mg/m³ (worker)		
DNEL (Derived No Effect Level) for the general population			
102-71-6 2,2',2"-nitr	ilotriethanol		
Oral Long ter population	m - systemic effects, general 13 mg/kg bw/day (general population)		

Printing date 27.05.2024 Version number 1 Revision: 27.05.2024

Trade name: MR® 703 W Developer white

		(Contd. of page 3)
Dermal	Long term - systemic effects, general population	3.1 mg/kg bw/day (general population)
Inhalative	Long term - systemic effects, general population	1.25 mg/m³ (general population)
	Long term - local effects, general population	1.25 mg/m³ (general population)

#### · PNECs

## 102-71-6 2.2'.2"-nitrilotriethanol

102-7 1-6 2,2 ,2 -intrilotriethanoi			
Aquatic compartment - freshwater	0.32 mg/L (freshwater)		
Aquatic compartment - marine water	0.032 mg/L (marine water)		
Aquatic compartment - water intermittent releases	5.12 mg/L (intermittent release water)		
Aquatic compartment - sediment freshwater	1.7 mg/kg sed dw (sediment fresh water)		
Aquatic compartment - sediment marine water	0.17 mg/kg sed dw (sediment marine water)		
Terrestrial compartment - soil	0.151 mg/kg dw (soil)		
Sewage treatment plant	10 mg/L (sewage treatment plant)		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection:

Filter P2

For good ventilation provide, this can be achieved by local or space exhaust. If the concentration lies over the job limit values, then, a certified respirator suitable for this purpose must be used.

Protection of hands:

Check the permeability prior to each anewed use of the glove.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

For the protection against chemicals in areas with heightened risk of injury (mechanical hazard) no recommendation for a suitable glove material can be given.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

# · Material of gloves

Rubber gloves

Recommended thickness of the material: > 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

Value for the permeation: Level  $\leq 6$ 

Supplier for suitable protection gloves:

ASD ArbeitsSicherheit Dortmund

Torstr. 101 - 37355 Niederorschel OT Rüdigershagen

Tel.: 02301 / 919543 - Fax: 02301 / 9453893

E-Mail: m.schnellhardt@t-online.de - http://www.arbeitssicherheitdortmund.de

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

## Eye protection:



Tightly sealed goggles

(Contd. on page 5)

Printing date 27.05.2024 Version number 1 Revision: 27.05.2024

Trade name: MR® 703 W Developer white

(Contd. of page 4)

• Body protection: Protective work clothing

# **SECTION 9: Physical and chemical properties**

· General Information

· Appearance:

Form: Fluid Colour: White

Odour: RecognisableOdour threshold: Not determined.

· pH-value at 20 °C:

· Change in condition

**Melting point/freezing point:** Undetermined. **Initial boiling point and boiling range:** 100 °C

· Flash point: Not applicable.

· Flammability (solid, gas): Not applicable.

· Decomposition temperature: Not determined.

· **Ignition temperature**: Product is not selfigniting.

• **Explosive properties:** Product does not present an explosion hazard.

· Explosion limits:

Lower:Not determined.Upper:Not determined.

· Vapour pressure at 20 °C: 23 hPa

Density at 20 °C:
 Relative density
 Vapour density
 Evaporation rate
 1.07 g/cm³
 Not determined.
 Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic: Not determined. Kinematic at 20 °C: 2.94 mm²/s

· Solvent separation test:

 Organic solvents:
 2.0 %

 Water:
 83.6 %

 VOC (EU)
 <0.1 %</td>

 Solids content:
 < 15.0 %</td>

• 9.2 Other information No further relevant information available.

# **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

(Contd. on page 6)

Printing date 27.05.2024 Version number 1 Revision: 27.05.2024

Trade name: MR® 703 W Developer white

(Contd. of page 5)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# **SECTION 11: Toxicological information**

11.1 Information on toxicological effects

LD/LC50 values relevant for classification:

102-71-6 2,2',2"-nitrilotriethanol

Oral LD50 8,000 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · General remarks:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability

The product is readily biodegradable (according to OECD criteria).

The biodegradability of the aqueous solution (1-3 %, washwater) amounts to > 90 %.

- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

The wash water (1-3% aqueous dilution of the product) may be added to the waste water treatment with the approval of the local water authority.

Water hazard class 1: weakly water-endangering

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

GB

Printing date 27.05.2024 Version number 1 Revision: 27.05.2024

Trade name: MR® 703 W Developer white

(Contd. of page 6)

## **SECTION 13: Disposal considerations**

#### · 13.1 Waste treatment methods

#### · Recommendation

Eliminate the pure, unchanged substance in accordance with local regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

## Waste disposal key:

For this product no waste key number can be specified, because only the intended purpose permits an allocation. The waste key number is to be specified in arrangement with the regional waste disposal.

The indications for Waste key reflect the pure unmodified product and are only a recommendation.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name · ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA · Class	Void	
· 14.4 Packing group · ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards: · Marine pollutant:	No	
· 14.6 Special precautions for user	Not applicable.	
· 14.7 Transport in bulk according to Ani of Marpol and the IBC Code	nex II Not applicable.	
· UN "Model Regulation":	Void	

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:
- · Waterhazard class: Water hazard class 1: slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

## · Relevant phrases

The wording of the listed risk phrases are those of the individual raw materials. H319 Causes serious eye irritation.

(Contd. on page 8)

Printing date 27.05.2024 Version number 1 Revision: 27.05.2024

Trade name: MR® 703 W Developer white

(Contd. of page 7)

#### · Recommended restriction of use

Existing national and local laws concerning chemicals are to be considered.

#### Department issuing SDS:

MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38

· Contact:

MR Chemie GmbH, Dep. safety data sheets, Tel.: +49/(0)2303/95151-38, QS@mr-chemie.de

#### · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

\* Data compared to the previous version altered.

\_ \_ \_