

PRODUCT INFORMATION

Penetrant Testing



MR® 670 F Piccolo-Pen

Product Characteristics



- Water washable penetrant fluorescent
- Penetrant Type I
- Sensitivity level 0.5 acc. EN ISO3452
- Crack indication colour yellow and yellow fluorescent
- Suitable for all metals (suitability for plastics and ceramics must be checked before use)
- Carrier medium Glycol

Minimum shelf life / Temperatures

3 years at storage temperature
Storage: + 5 °C - + 45 °C
Application: - 10 °C - + 50 °C



Approvals / Specification



- EN ISO 3452-2
- ASME Code V, Art. 6
- ASTM E165
- RCC-M
- PMUC
- VDA236-150


Further Information

Process description according to EN ISO 3452-1 on request or on www.mr-chemie.de/en. For further information see Material Safety Data Sheet and certificate 3.1. For additional equipment please visit our Homepage or contact our sales team.

Suggested Products

Pre-cleaner: MR® 79, MR® 85, MR® 88, MR® 3001, MR® 3002
Remover: Water
Developer: MR® 70, MR® 703 W (+5 °C), MR® 81 T-R
Test block: Reference-Testblock 1 and 2, ASTM Testblock

Delivery Form



technical changes reserved!